



- 1.SHELL: MATERIAL:BRASS, C2680 THK=0.3±0.01.  
FINISH: 60u" NI PLATED.
- 2.CONTACT: MATERIAL:PHOSPHOR BRONZE  
JIS 5191R-H,THK=0.2±0.01.  
FINISH: 3u" MIN GOLD FLASH ON CONTACT AREA  
120u" MIN SN-PB ON SOLDER TAIL AND  
60u" MIN NI UNDERPLATED ON ENTIRE CONTACT.
- 3.HOUSING: MATERIAL: LCP+15%GF,UL 94V-0.
- 4.GENERAL TOLERANCE: ±0.15

4	SHELL	PHOSPHOR BRONZE(C5191 )	NICKEL PLATED	1	
3	INSULATOR	LCP	BLACK	1	
2	PIN B	PHOSPHOR BRONZE(C5191 )	30U"GOLD/TIN	4	
1	PIN A	PHOSPHOR BRONZE(C5191 )	30U"GOLD/TIN	4	
Item	Name	Material	Finish	Q'ty	Note

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PJECTION

X. ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±



**ORDER INFORMATION**

MSB-PS-8C-LF  
SERIES | LEADFREE  
8 PIN C TYPE  
SOLDER  
MALE

DESCRIPTION: MiniUSB 8PIN (M) 雙排 (方形)