



Electrical Properties

- 1.100% Test(Open Short Miss Wire)
- 2.Contact Resistance: 3Ω Maximum
- 3.Insulation Resistance: 10MΩ Minimum
- 4.Hi-Pot: 300V 10ms

P1	Red	P2	1
4	Yellow		2
5	White		3
8			
		<u>PIN OUT</u>	

ITEM	PARTS NAME	SPECIFICATION STANDARD	Q'TY
6	H.S. TUBE	∅7.0mm Color:Black	1PCS
5	WIRE	PC Plug RJ45 8P8C Pin 鍍金 透明色 多芯單芯共用 0.9線孔	1PCS
4	TERMINAL	PVC UL60C 45P Black N16P	6g
3	HOUSING	圓柱型鐵殼 OD6.0x50mm	1PCS
2	TERMINAL	傳感器 DS18B20 (-55°C~+125°C)	1PCS
1	CABLE	UL2725#28x3C OD3.0 L=4500mm Black	1PCS

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

PPOJECTION



ORDER INFORMATION

RJTHM-080328-M4M5-LF
SERIES | LEADFREE
8P3C | 28AWG | 4500mm
MALE

DESCRIPTION: Round Cable RJ45 8P8C To DS18B20 UL2725 #28x3C OD:3.0mm L=4500mm 黑