







1. MATERIAL

INSULATION: THERMOPLASTIC UL94V-0
 COLOR: BLACK.
 CONTACT: BRASS
 SHELL: ERASS

2. PLATING

CONTACT: CONTACT PLATED 10u" GOLD,
 SHELL: Nickel 100u"

3. SPECIFICATION

Current rating: 5A / Voltage rating: 24Vdc.
 OPERATING TEMPERATURE: -20. C TO 105. C.
 INSULATION RESISTANCE: 1000 MEGAOHMS MIN.
 DIELECTRIC STRENGTH: 500V AC MIN.

TYPE A

Item	Description	Material	UL File No.
1	Insulation	1403G6	E130155
2	Pin	MS A3250 C3604 BG	
3	Shell	C3604	
4	O-Ring	NBR	

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X. ±
 .X ±
 .XX ±
 .XXX ±
 ANG ±



ORDER INFORMATION

M12-SS-03-LF
 SERIES | T LEADFREE
 03 WAY
 SOLDER
 FEMALE

DESCRIPTION: M12-3(母)防水頭