

## MECHANICAL

### INSULATOR MATERIAL:

PBT & Glass-fibre reinforced  
UL-94-V0

### CONTACT:

Phosphor bronze, Gold Plated

## ELECTRICAL $\triangle B$

### CURRENT RATING:

5 Amp

### WITHSTANDING VOLTAGE:

AC 500V Min. (for one minute)

### INSULATION RESISTANCE:


500M $\Omega$  Min.(at 500V DC)

### CONTACT RESISTANCE:

25m $\Omega$  Max. mated

### WORKING TEMPERATURE:

-55°C to +105°C



RoHS Compliant

TOLERANCES ARE

DRAWING BY CY

X.  $\pm$

CHECKED BY GENIUS

.X  $\pm$  0.30

UNIT / mm

SCALE 1 : 1

.XX  $\pm$  0.20

DATE

.XXX  $\pm$  0.10

ANG  $\pm$  3.0°

SIZE A4

PPOJECTION

ORDER INFORMATION

V35-SRL-34-LF  
SERIES | LEADFREE  
34 WAY  
LONG  
DIP 90°  
FEMALE

DESCRIPTION: V.35 PCB RIGHT ANGLE FEMALE HIGH PROFILE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com