



NOTES:

1. THIS IS MMBX JACK FOR SMT.
2. ELECTRICAL SPEC:
 - 2.1 IMPEDANCE: 50 OHMS NOMINAL.
 - 2.2 FREQUENCY RANGE: 0~12.4 GHz.
 - 2.3 INSULATION RESISTANCE: 1000 MEGOHMS MIN.
 - 2.4 DIELECTRIC WITHSTANDING VOLTAGE: 1000 VOLTS MIN.
 - 2.5 CONTACT RESISTANCE:
 - 2.5.1 CENTER CONTACT: 4.0 MILLIOHMS.
 - 2.5.2 OUTER CONTACT: 2.5 MILLIOHMS.
3. MECHANICAL SPEC:
 - 3.1 COUPLING METHOD: SLIDE-ON COUPLING.
 - 3.2 DURABILITY: 100 CYCLES.
4. ENVIRONMENTAL SPECE:
 - 4.1 TEMPERATURE RANGE: -55°C TO +155°C.

4	CAP	PTFE	NONE	1
3	PIN CONTACT	BRASS	GOLD 0.20um OVER NICKEL	1
2	INSULATOR	LCP	NONE	1
1	BODY	BRASS	NONE	1
ITEM	NAME	SPEC.	FINISH	Q'TY

RECOMMEND SMT SOLDERING PAD

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES
煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

TOLERANCES ARE

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

PPOJECTION



ORDER INFORMATION

MMBX-JVC-50-LF

SERIES | | | LEADFREE
| | | 50 OHM
| | | COVER
| | | 180°SMT
| | | JACK

DESCRIPTION: MMBX JACK FOR SMT