




▽ PITCH 2.54MMX7.62MM I.D.C. DIP PLUG
FOR PITCH 1.27MM CENTER FLAT RIBBON CABLE

MATERIAL & FINISH

*INSULATOR:PBT+GLASS FIBER UL 94V-0

*CONTACT:BRASS

*FINISH: GOLD-PLATED OVER NICKEL
SPECIFICATIONS

*CURRENT RATING: 1A AC,DC

*VOLTAGE RATING: 250V AC,DC

*TEMPERATURE RANGE: -40°C TO +105°C

*CONTACT RESISTANCE: 20MΩ MAX

*INSULATION RESISTANCE: 1,000MΩ MIN

*WITHSTANDING VOLTAGE: 500V AC/MIN

PART NO	DIM A	DIM B	PART NO	DIM A	DIM B
IP03-C2-08	7.62	15.42	IP03-C2-24	27.94	35.74
IP03-C2-10	10.16	17.96	IP03-C2-26	30.48	38.28
IP03-C2-14	15.24	23.04	IP03-C2-28	33.02	40.82
IP03-C2-16	17.78	25.58	IP03-C2-34	40.64	48.44
IP03-C2-18	20.32	28.12	IP03-C2-40	48.26	56.06
IP03-C2-20	22.86	30.66			

DIMENSIONS:MM

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±
.X ± 0.20
.XX ± 0.10
.XXX ±
ANG ±



ORDER INFORMATION

IP03-C2-xx-LF
SERIES | LEADFREE
08~40WAY
TWO TYPE

DESCRIPTION: IDC DIP PLUG PITCH2.54mm*7.62mm