

Recommended P.C.B. Layout

## SPECIFICATIONS

- \* Current Rating : 1 Amps
- \* Insulator resistance: 5000 Megohms min.
- \* Dielectric withstanding: AC 500 V
- \* Operating Temperature:  $-40^{\circ}$   $-+105^{\circ}$ C
- \* Max Processing Temp:  $230^{\circ}$  for 30~60 seconds  
( $260^{\circ}$  for 10 seconds)
- \* Contact Material: Phosphor bronze
- \* Housing: L.C.P (UL 94 V-0)

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

**RoHS Compliant**

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1


DATE

SIZE A4

TOLERANCES ARE

X.  $\pm$   
.X  $\pm$   
.XX  $\pm$   
.XXX  $\pm$   
ANG  $\pm$

PJECTION



### ORDER INFORMATION

YA-D20-1Xxx-LF  
SERIES | LEADFREE  
1X03:03WAY  
1X50:50WAY  
HIGH 2.0mm  
DIP 180°

DESCRIPTION: 1.27X1.27mm SOCKET LOW PROFILE 2.0mm DIP TYPE