





ELECTRICAL PROPERTIES:

1. 100% Open Short Mis -Wire Test
2. Contact Resistance: 2 ohm max
3. Insulation Resistance: 10mega ohm min
4. Hipot test: DC 100V 10ms

④	PVC 45P 黑色 (ROHS)	12G
③	USB B/M G/F 殼鍍鎳 白膠芯 (ROHS)	1PCS
②	USB A/M G/F 殼鍍鎳 白膠芯 (ROHS)	1PCS
①	UL2725 #28/1P+#28/2C+AE OD:3.5 BLACK (ROHS)	1PCS
IO.	DESCRIPTION	QTY

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

TOLERANCES ARE

X. ±


.X ±

.XX ±

.XXX ±

ANG ±

PPOJECTION



ORDER INFORMATION

UBX2-4A4B28-M20C-LF

SERIES

LEADFREE

200mm

MALE TO MALE

28 AWG

4 PIN A TYPE TO 4 PIN B TYPE

DESCRIPTION: USB AM/BM L=200mm