

CAT. NO.	PIN	SCHEMATIC
DCJ-DPB-20	$\phi 2.0$	1
DCJ-DPB-25	$\phi 2.5$	3

T:1.6 Dimensions of PC board holes

Tolerance :  $\pm 0.1$ (Printed-top view)

UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL:  $\pm 0.3$

LTR	PART NAME	QTY	MATERIAL	REMARK
6	HOUSING	1	PA66	
5	AXIS SUPPORT	1	BRASS	MB:Cu Ni PLATED
4	PIN	1	H59 BRASS	MB:Cu Ni PLATED
3	SPRING	1	BRONZE	MB:Cu Cu/Sn PLATED
2	CURVE PIECE	1	H62 BRASS	MB:Cu Cu/Sn PLATED
1	FLAT PIECE	1	H62 BRASS	MB:Cu Cu/Sn PLATED

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS


UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X.  $\pm$   
.X  $\pm$   
.XX  $\pm$   
.XXX  $\pm$   
ANG  $\pm$

P PROJECTION



ORDER INFORMATION

DCJ-DPB-xx-LF  
SERIES | | LEADFREE  
| | 20:2.00  
| | 25:2.50  
DIP 90° | BACK  
| PANEL

DESCRIPTION: DC POWER JACK