

T: 1.6 Dimensions of PC board holes  
Tolerance : ±0.05(Printed-top view)

CAT. NO.	PIN	SCHEMATIC
DCJ-R40-20	∅2.0	
DCJ-R40-25	∅2.5	
DCJ-R40-165	∅1.65	
DCJ-R40-235	∅2.35	

LTR	PART NAME	QTY	MATERIAL	REMARK
5	PIN	1	H59(COPPER ALLOY)	Cu/Sn PLATED
4	CONTACT FOOT	1	C2680	Ag PLATED
3	SPRING	1	C5191	Ag PLATED
2	CURVE PIECE	1	C2680	Ag PLATED
1	HOUSING	1	PA66	BLACK

UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL: ±0.3

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

X.±

CHECKED BY GENIUS

.X±

UNIT / mm

SCALE 1:1

.XX±


.XXX±

ANG±

DATE

SIZE A4

P PROJECTION



ORDER INFORMATION

DCJ-R40-xx-LF  
SERIES | LEADFREE  
20:2.0∅  
235:2.35∅  
POST 4.0mm  
DIP 90°

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: DC POWER JACK