

T:1.6 Dimensions of PC board holes
Tolerance : ±0.1(Printed-top view)

CAT. NO.	PIN	SCHEMATIC
DCJ-RKPN-20	φ2.0	
DCJ-RKPN-25	φ2.5	
DCJ-RKPN-30	φ3.0	

6	HOUSING	1	PBT 4815	UL-94V0(BLACK)
5	COVER	1	PBT 4815	UL-94V0(BLACK)
4	PIN	1	C2680	MB:Cu Cu/Sn PLATED
3	SHUNT TERMINAL	1	C2680 t=0.5	MB:Cu Cu/Sn PLATED
2	TIP SPRING	1	C5191 t=0.25	MB:Cu Cu/Sn PLATED
1	CENTER PIN TERMINAL	1	C2680 t=0.5	MB:Cu Cu/Sn PLATED
LTR	PART NAME	QTY	MATERIAL	REMARK


UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL: ±0.3

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES
煜倫股份有限公司
www.morethanall.com

DRAWING BY CY		X.±
CHECKED BY GENIUS		.X±
UNIT/mm	SCALE 1:1	.XX±
DATE		.XXX±
		ANG±
SIZE A4	PJECTION	



ORDER INFORMATION

DCJ-RKPN-xx-LF		
SERIES		LEADFREE
		20:2.00
		25:2.50
		30:3.00
DIP 90°		
	PANEL	
	KINK	

DESCRIPTION: DC POWER JACK