

- SPECIFICATIONS:
- CONTACT RESISTANCE : 20m OHM.
 - INSULATION RESISTANCE : DC 500V 100M OHM MIN.
 - VOLTAGE WITHSTANDING : AC 500V 1 MINUTE.
 - INSERTION FORCE : 4KG MAX.
 - WITHDRAWAL FORCE : 1 - 5 KG.
 - LIFE TEST : 5,000 CYCLES MIN. AFTER TESTING , CONTACT RESISTANCE SHALL NOT EXCEED 100m OHM.
 - CURRENT RATING : AC : 100V 2A.
DC : 24V 1A.
 - Unless other specified, the tolerance is ± 0.2 mm

P/N	PART NAME	Q'TY	MATERIAL	PLATING	REMARKS
4.	CONTACT TERMINAL	8	BSR-H/2 0.7t	TIN	
3.	EARTH TERMINAL	1	PBSR 0.25t	TIN	
2.	COVER	1	P.B.T.		UL94V-0
1.	BODY	1	P.B.T.		UL94V-0

RoHS Compliant

TOLERANCES ARE



DRAWING BY CY

CHECKED BY GENIUS


UNIT / mm SCALE 1 : 1

DATE


SIZE A4

- X, \pm
- .X \pm
- .XX \pm
- .XXX \pm
- ANG \pm

PJECTION



ORDER INFORMATION



煜倫股份有限公司

www.morethanall.com

DESCRIPTION: