



T:1.6 Dimensions of PC board holes
 Tolerance : ± 0.1 (Printed-top view)

CAT. NO.	PIN	SCHEMATIC
DCJ-D-20	$\phi 2.0$	
DCJ-D-25	$\phi 2.5$	

6	COVER	1		
5	CONTACT FOOT	1	BRASS	MB:Cu Cu/Sn PLATED
4	PIN	1	H59 BRASS	MB:Cu Ni PLATED
3	SPRING	1	65Mn STEEL	MB:Cu Cu/Sn PLATED
2	FLAT PIECE	1	H62 BRASS	MB:Cu Cu/Sn PLATED
1	HOUSING	1	PBT/PASS	
LTR	PART NAME	QTY	MATERIAL	REMARK

UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL: ± 0.3

UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL: ± 0.3

RoHS Compliant

TOLERANCES ARE



DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, \pm
 X, \pm
 .XX \pm
 .XXX \pm
 ANG \pm

PPOJECTION



ORDER INFORMATION

DCJ-D-xx-LF
 SERIES | LEADFREE
 20:2.0 ϕ
 25:2.5 ϕ
 DIP 180 $^{\circ}$

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: DC POWER JACK