

CAT. NO.	PIN	SCHEMATIC
DCJ-SPE13-20	Ø2.0	1
DCJ-SPE13-25	Ø2.5	3
		2

6	COVER	1	PBT 4815	UL-94V0(BLACK)
5	AXIS SUPPORT	1	C2680	MB:Cu Sn PLATED
4	PIN	1	C2680	MB:Cu Ni PLATED
3	SPRING	1	C5191	MB:Cu Sn PLATED
2	FLAT PIECE	1	C2680	MB:Cu Sn PLATED
1	HOUSING	1	PBT 4815	UL-94V0(BLACK)
LTR	PART NAME	QTY	MATERIAL	REMARK

UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL: ±0.3

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±


.X ±

.XX ±

.XXX ±

ANG ±

P PROJECTION



ORDER INFORMATION

DCJ-SPE13-xx-LF  
SERIES | | | LEADFREE  
| | | 20:2.0Ø  
| | | 25:2.5Ø  
SOLDER | | | HIGH 13.4mm  
| | | EAR  
| | | PANEL

DESCRIPTION: DC POWER JACK