

ELECTRICAL SPECIFICATIONS:

VOLTAGE RATING: AC 500V

WITH STANDING VOLTAGE: AC 1,000V ONE MINUTE

INSULATION RESISTANCE: 1,000MΩ MIN AT DC 500V

CONTACT RESISTANCE: 3MΩ MAX AT DC 1A

FREQUENCY RANGE: 0-4,000MHZ

VSWR: 1.2 MAX 0-4GHz

8	GASKET	SI-RUBBER	ORANGE	1
7	RETAINING	BRASS	NICKEL	1
6	SHELL	BRASS	NICKEL	1
5	FERRULE	BRASS	NICKEL	1
4	GROUND RING	BRASS	NICKEL	1
3	DIELECTRIC	DELFIN	WHITE	1
2	PIN	BRASS	GOLD	1
1	BODY	BRASS	NICKEL	1
NO	DESCRIPTION	MATERIAL	FINISH	QTY

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X. ± 0.30

CHECKED BY GENIUS

.X ± 0.30

UNIT / mm

SCALE 1 : 1

.XX ± 0.20


.XXX ± 0.10

ANG ± 1°

DATE

SIZE A4

PPOJECTION



ORDER INFORMATION

N-PC-213-LF
SERIES | LEADFREE
RG213
CRIMP
MALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: N MALE CRIMP