

T:1.6 Dimensions of PC board holes
Tolerance : ±0.1(Printed-top view)

CAT. NO.	PIN	SCHEMATIC
DCJ-R40AM-20	φ2.0	
DCJ-R40AM-25	φ2.5	
DCJ-R40AM-165	φ1.65	

7	COAT	1	ALOARY	MB:Cu Ni PLATED
6	CONTACT FOOT	1	BRASS	MB:Cu Ni PLATED
5	PIN	1	BRASS	MB:Cu Ni PLATED
4	CONTACT FOOT	1	BRASS	MB:Cu Ag PLATED
3	CURVE PIECE	1	BRASS	MB:Cu Ag PLATED
2	SPRING PIECE	1	BRONZE	MB:Cu Ag PLATED
1	HOUSING	1	PBT	
LTR	PART NAME	QTY	MATERIAL	REMARK

UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL: ±0.3

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS


UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

P PROJECTION



ORDER INFORMATION

DCJ-R40AM-xx-LF
SERIES | | | LEADFREE
165:1.65Ø
20:2.0Ø
25:2.5Ø
DIP 90° METAL
POST 4.0mm A TYPE

DESCRIPTION: DC POWER JACK

煜倫股份有限公司

www.morethanall.com