

CAT. NO.	PIN	SCHEMATIC
DCJ-SPBT5-20	∅2.0	1
DCJ-SPBT5-25	∅2.5	2 3

LTR	PART NAME	QTY	MATERIAL	REMARK
6	HOUSING	1	PBT 4815	UL-94V0(BLACK)
5	AXIS SUPPORT	1	C2680	MB:Cu Ni PLATED
4	PIN	1	C2680	MB:Cu Ni PLATED
3	SPRING	1	C5191	MB:Cu Sn PLATED
2	CURVE PIECE	1	C2680	MB:Cu Sn PLATED
1	FLAT PIECE	1	C2680	MB:Cu Sn PLATED


UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL: ±0.3

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES
煜倫股份有限公司
www.morethanall.com

DRAWING BY CY		X.± .X± .XX± .XXX± ANG±
CHECKED BY GENIUS		
UNIT / mm	SCALE 1:1	
DATE		
SIZE A4	PJECTION	



ORDER INFORMATION

DCJ-SPBT5-xx-LF
SERIES | | LEADFREE
20:2.0∅
25:2.5∅
SOLDER | | THREAD 5.6mm
BACK
PANEL

DESCRIPTION: DC POWER JACK