



**SPECIFICATIONS:**

1. CONTACT RESISTANCE : 20m OHM MAX.
2. INSULATION RESISTANCE : 300M OHM MIN. AT DC 500V.
3. VOLTAGE WITHSTANDING : AC 1000V FOR ONE MINUTE.
4. INSERTION FORCE : 4.0KG MAX.
5. WITHDRAWAL FORCE : 1 - 3.5KG.
6. CURRENT RATING : AC: 100V 2A  
DC: 20V 1A

5.	RIVET	1	AL	NICKEL PLATED	
4.	CONTACT TERMINAL	7	BSR-H/2 0.7t	TIN	
3.	EARTH TERMINAL	1	PBSR 0.25t	TIN	
2.	INSULATOR	1	P.B.T.		UL94V-0
1.	SOCKET CASE	1	SPCC-SD 0.4t	NICKEL PLATED	
P/N	PART NAME	Q'TY	MATERIAL	PLATING	REMARKS

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT/mm SCALE 1:1

DATE

SIZE A4

X, ±  
.X ± 0.30  
.XX ± 0.20  
.XXX ±  
ANG ±

P PROJECTION



**ORDER INFORMATION**

DJ-D12S-07-LF  
SERIES | LEADFREE  
| 07 WAY  
| SPRING  
| PCB LAYOUT BIGGEST WIDTH 12.0mm  
DIP180°

DESCRIPTION: