


RECOMMENDED PCB LAYOUT

Frequency Range :DC-6GHZ  
 VSWR: 1.2MAX  
 Working voltage :500V  
 Dielectric withstand voltage  
 1000V AC AT minute  
 Insulation Resistance:5000  
 Megaohs min AT DC 500V  
 Durability:500 Matings  
 Temperature Range:-40C+85C



3	DIELECTRIC	TEFLON	NONE	1
2	PIN	BRASS	GOLD	1
1	BODY	BRASS	GOLD	1
NO	DESCRIPTION	MATERIAL	FINISH	QTY

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES  
 煜倫股份有限公司

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

0.5-5 =±0.2  
 5-30 =±0.4  
 30-120 =±0.6  
 120-315 =±1  
 315-1000 =±1.6  
 1000-2000 =±2.4

SIZE A4

PPOJECTION



**ORDER INFORMATION**

**SMA-JW-50-LF**  
 SERIES | T | LEADFREE  
 50 OHM  
 90° SMT  
 JACK

DESCRIPTION: SMA female pcb mount

[www.morethanall.com](http://www.morethanall.com)