



MA 003A (DB9M/HD15F ADAPTOR)

PIN OUT: 09Male

15Female

1	-----	1
2	-----	2
3	-----	3
4	-----	13
5	-----	14
6	-----	6
7	-----	7
8	-----	8
9	-----	10+11
G	-----	G

Label: orange color with white character
 One side: PS2 VGA ADAPTORS D9/HD15
 The other side: MINI ADAPTER
SPECIFICATION
 INSULATOR: PBT Glass fibre reinforced UL 94 V0
 CONTACT: Brass
 CONTACT PLATING: Gold plated over nickel
 SHELL: Tin plated shell
 CURRENT RATING: 3 AMP
 DIELECTRIC STRENGTH: 500V AC for one minute
 INSULATOR RESISTANCE: 500MΩ min at 500V DC
 TEMPERATURE: -25°C—+105°C

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

DRAWING BY CY

X, ±

CHECKED BY GENIUS

X, ±

UNIT / mm

SCALE 1 : 1

.XX ±

DATE

.XXX ±

ANG ±

SIZE A4

PPOJECTION



ORDER INFORMATION

DBHD-ES-0915-LF

SERIES

LEADFREE

09 TO 15 WAY

MALE TO FEMALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: