





Circuit Diagram



Performance:
Meets C3 Standard.

Materials:
Body : Fireproof ABS UL-94V0
Jack : 6P6C 6 micro inches gold plated
(Through-Pin)

Electrical Specifications:
Insulation Resistance : 500M ohms (min.)
Contact Resistance : 20m ohms (max.)
Current Rating : 1.5 Amps .
DC Resistance : 0.1 ohms (max.)
Withstanding Voltage : 1000 VAC RMS @ 60Hz / 1 min.

Mechanical Specifications:
Jack Insertion Cycle : Over 2000 Cycles (min.)
Operation Temperature : -40 ° ~ +70°

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

TOLERANCES ARE

X, ±


.X ±

.XX ±

.XXX ±

ANG ±

PPOJECTION



ORDER INFORMATION

RJX2-FSC3PN28WH-0606-LF

SERIES FEMALE TO FEMALE 180°
C3
PANEL
WHITE
LONG 28mm
6P6C
LEADFREE

DESCRIPTION: &,1/,1(&283/(5873X