

备注:

1. 产品规格:

- 1-1. 插入力: 35N MAX.
- 1-2. 拔出力: 10N MIN. INITIAL 8-20N AFTER 10000 CYCLES
- 1-3. 额定电流: 1.5A
- 1-4. 额定电压: 30V
- 1-5. 耐久性: 10000 CYCLES MIN.
- 1-6. 耐电压: 500V AC MIN.
- 1-7. 接触阻抗: 30mΩ MAX. INITIAL; 40mΩ MAX AFTER 10000 CYCLES
- 1-8. 绝缘电阻: 1000MΩ MIN
- 1-9. 工作温度: -30° TO +80°

2. 材质:

- 2. 1胶芯: LCP UL94V-0
- 2. 2端子: C2680R-H, 镍底, 镀金G/F
- 2. 3外壳: SUS / C2680R-H, 表面SN 50~80 μ

3. 所用材质须符合RoHS要求

4. 重点尺寸标识“▲”符号

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ± 0.25
.XX ± 0.20
.XXX ± 0.10
ANG ±

PPOJECTION



ORDER INFORMATION

MISB-SWP40-5B-LF

SERIES | | LEADFREE
5 PIN B TYPE
POST 4.0mm
90°SMT
FEMALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: MICRO 5P/F B TYPE SMT 有柱