

E/E1	TUBE	$\phi 8.0 / \phi 3.0$	1/1PCS
D	BRAID	168C/0.12T	1PCS
C/C1	WIRE	UL1571 28# 0.6 / UL1571 28# 0.8	21/4PCS
B4	TERMINAL	PNM-T-28 OR EQU	4PCS
A4	HOUSING	PNM-H-04 1.25PITCH OR EQU	1PCS
B3	TERMINAL	PH-T-24 OR EQU	4PCS
A3	HOUSING	PH-H-04 2.0PITCH OR EQU	1PCS
B2	TERMINAL	DF13-T-26 OR EQU	20PCS
A2	HOUSING	DF13-H-2X20 1.25C	1PCS
B1	TERMINAL	FIX-TG-30 OR EQU	21PCS
A1	HOUSING	FIX-HL-30 (FIX-HL)1.0PITCH OR EQU	1PCS
NO	DESCRIPTION	SPECIFICATION	Q'ty

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS


UNIT / mm SCALE 1 : 1

DATE

SIZE A4

PJECTION

X, ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±



ORDER INFORMATION

DF13FIXL-B203028-A45CA

SERIES

450mm  
FEMALE TO MALE  
28 AWG  
40 TO 30 WAY

煜倫股份有限公司

www.morethanall.com

DESCRIPTION:

CONN1			CONN2
PIN NO.	FUNCTION	COLOR	PIN NO.
1	NC		-
2	NC		-
3	NC		-
4	GND	BLACK	5
5	twist LVDS0_Z_D0-	BLUE	7
6		LVDS0_Z_D0+	WHITE
7	GND	BLACK	11
8	twist LVDS0_Z_D1-	BLUE	13
9		LVDS0_Z_D1+	WHITE
10	GND	BLACK	17
11	twist LVDS0_Z_D2-	BLUE	19
12		LVDS0_Z_D2+	WHITE
13	GND	BLACK	23
14	twist LVDS0_Z_CK-	BLUE	25
15		LVDS0_Z_CK+	WHITE
16	GND	BLACK	29
17	twist LVDS0_Z_D3-	BLUE	31
18		LVDS0_Z_D3+	WHITE
19	GND	BLACK	35
20	NC		-
21	NC		-
22	NC		-
23	NC		-
24	NC		-
25	NC		-
26	VDD	RED	4
27	VDD	RED	4
28	VDD	RED	3
29	VDD	RED	2
30	VDD	RED	1

CONN3			CONN4
PIN NO.	FUNCTION	COLOR	PIN NO.
1	VDD	RED	1
2	EN	WHITE	3
3	PWM	GREEN	4
4	GND	BLACK	2

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES  
煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1


DATE

SIZE A4

TOLERANCES ARE

X. ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±

PJECTION 



ORDER INFORMATION

DF13FIXL-B203028-A45CA

SERIES

450mm

FEMALE TO MALE

28 AWG

40 TO 30 WAY

DESCRIPTION: