

P.C.B. LAYOUT

1. MATERIALS AND FINISH

SHELL: STEEL MATERIAL, FRONT SHELL TIN FINISHED
 BACK SHELL TIN FINISHED
 DIMPLES ON PLUG ONLY

INSULATOR: PBT THERMOPLASTIC, 30% GLASS FILLED, UL 94V-0, BLACK
 CONTACT: COPPER ALLOY, FULL GOLD FLASH

2. SPECIFICATION

CONTACT CURRENT RATING : 5.0 A
 CONTACT RESISTANCE : 10 mΩ MAX.
 DIELECTRIC WITHSTANDING VOLTAGE : 1000 V AC MIN.
 INSULATION RESISTANCE : 5GΩ MIN.
 TEMPERATURE RATING : -55°C ~ +125°C

| No | A | B | C |
|----|-------|-------|-------|
| 09 | 16.30 | 25.00 | 30.80 |
| 15 | 24.60 | 33.30 | 39.20 |
| 25 | 38.40 | 47.00 | 53.00 |
| 37 | 54.80 | 63.50 | 69.30 |

RoHS Compliant

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS


UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
 .X ± 0.30
 .XX ± 0.25
 .XXX ± 0.15
 ANG ± 2°

P PROJECTION



ORDER INFORMATION

DR72-SZJ-xx-LF

SERIES
 LEADFREE
 09-37 WAY
 JACKSCREW
 NUT
 CLIP
 FEMALE

DESCRIPTION: D-SUB 90°, FEMALE, L PIECE, 7.2 mm, Machine Pin