



SPECIFICATIONS

Electrical



Current Rating: 2.5A AC, DC
Voltage Rating: 250V AC/ max.
Operating Temp.: -25°C ~ +85°C
Insulation Resistance: 1000MΩ/ min.
Dielectric Withstanding Voltage: 800V AC/ min.
Contact Resistance: 10mΩ/ max.

Material

Terminal Material: Brass, Copper-Undercoated,/ Tin
Material: Nylon 66, UL94V-0



RECOMMENDED P.C.BOARD HOLE DIMM.



Poles	Dimension mm (in.)	
	A	B
2	2.50 (0.098)	7.50 (0.295)
3	5.00 (0.197)	10.00 (0.394)
4	7.50 (0.295)	12.50 (0.492)
5	10.00 (0.394)	15.00 (0.591)
6	12.50 (0.492)	17.50 (0.689)
7	15.00 (0.591)	20.00 (0.787)
8	17.50 (0.689)	22.50 (0.886)
9	20.00 (0.787)	25.00 (0.984)
10	22.50 (0.886)	27.50 (1.082)
11	25.00 (0.984)	30.00 (1.181)
12	27.50 (1.082)	32.50 (1.280)
13	30.00 (1.181)	35.00 (1.378)
14	32.50 (1.280)	37.50 (1.476)
15	35.00 (1.378)	40.00 (1.575)



煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

TOLERANCES ARE

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

P PROJECTION



ORDER INFORMATION

EH-R-xx-LF
SERIES | LEADFREE
02~15WAY
DIP 90°

DESCRIPTION: 2.5mm Wire-to-Board Header DIP 90° Type