



▼ CE PITCH 2.54MM I.D.C. CARD EDGE CONNECTOR
FOR PITCH 1.27MM CENTER FLAT RIBBON CABLE

MATERIAL & FINISH

*INSULATOR: PBT+GLASS FIBER UL 94V-0

*CONTACT: BRASS

*FINISH: GOLD-PLATED OVER NICKEL
SPECIFICATIONS

*CURRENT RATING: 1A AC,DC

*VOLTAGE RATING: 250V AC,DC

*TEMPERATURE RANGE: -44°C TO +105°C

*CONTACT RESISTANCE: 20MΩ MAX

*INSULATION RESISTANCE: 1,000MΩ MIN

*WITHSTANDING VOLTAGE: 500V AC/MIN

DIMENSIONS:MM

PART NO	DIM A	DIM B	PART NO	DIM A	DIM B	PART NO	DIM A	DIM B
E-C2-10	10.16	22.03	E-C2-26	30.48	42.40	E-C2-50	60.96	72.90
E-C2-14	15.24	27.10	E-C2-34	40.64	52.60	E-C2-56	68.58	80.54
E-C2-16	17.78	29.60	E-C2-40	48.26	60.22	E-C2-60	73.66	85.43
E-C2-20	22.86	34.80	E-C2-44	53.34	65.30	E-C2-64	78.74	90.51

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

P PROJECTION

X. ±
.X ±
.XX ±
.XXX ±
ANG ±



ORDER INFORMATION

E-C2-xx-LF
SERIES | LEADFREE
10-64WAY
TWO TYPE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: