



SPECIFICATION

1. INSULATION RESISTANCE : DC 500V 500MΩ 以上
2. VOLTAGE WITHSTANDING : AC 1.2KV 1 min.
3. CONTACT RESISTANCE : AC 1000V 20mΩ MAX.(使用測具0.8 ±0.01)
4. INSERTION FORCE : 0.5Kg~3Kg
WITHDRAWAL FORCE : 0.3Kg~3Kg
5. FREQUENCY RANGE: 50MHz TO 850 MHz
6. TIGHTEN HEX NUT DOWN TO 4.5 IN-LBS.±0.5 IN-LBS
7. BODY TO BRACKET CLINCH MUST BE ABLE TO WITHSTAND 7.5 IN-LBS.OF TORQUE MIN
8. THE INSULATOR MUST NOT DEFORM OR DISCOLOR WHEN EXPOSED TO TEMPERATURES OF 200°C FOR 5 SECS.AND170°C FOR 30 SECS.
9. 絕緣套管膠料採用UL認證的

MATERIALS AND FINISHES

ON	DESCRIPTION	MATERIAL	PLATING
1	BODY	BRASS	NICKEL
2	DIELECTRIC	TEFLON	-
3	PIN	PHOSPHOR BRONZE	GOLD

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES
煜倫股份有限公司

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
X, ±
.XX ±
.XXX ±
ANG ±

PPOJECTION



ORDER INFORMATION

F-JE17-75-LF
SERIES | LEADFREE
75 OHM
EDGE CLIP 1.7mm
JACK

DESCRIPTION:

www.morethanall.com