

P. C. B . LAYOUT

A: 5.50 mm
 B: 2.00 mm
 C: 1.60 mm

MATERIAL

HOUSING : NY6T, UL94V-0
 CAP : NY6T, UL94V-0
 CONTACT : COPPER ALLOYS
 PLATED : GOLD FLASH
 COLOR : BLACK

SPECIFICATION

CURRENT : 1A
 OPERATING TEMPERATURE: -55° C TO +105° C
 CONTACT RESISTANCE : 20 MILLIOHMS MAX
 INSULATION RESISTANCE: 1000 MEGAOHMS MIN
 WITHSTANDING VOLTAGE : 500 V AC/minute

CONTACTS			
	2×12	2×25	2×38
	2×13	2×26	2×39
	2×14	2×27	2×40
	2×15	2×28	2×41
2×03	2×16	2×29	2×42
2×04	2×17	2×30	2×43
2×05	2×18	2×31	2×44
2×06	2×19	2×32	2×45
2×07	2×20	2×33	2×46
2×08	2×21	2×34	2×47
2×09	2×22	2×35	2×48
2×10	2×23	2×36	2×49
2×11	2×24	2×37	2×50

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS


UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
 .X ± 0.38
 .XX ± 0.25
 .XXX ±
 ANG ± 5°

P PROJECTION



ORDER INFORMATION



DESCRIPTION:

煜倫股份有限公司

www.morethanall.com