




RECOMMENDED PCB LAYOUT



$$\text{FPC/FFCT} = 0.30 \pm 0.05$$

MATERIAL

INSULATOR: GLASS-REINFORCED THERMOPLASTIC.

CONTACT: COPPER ALLOY.

PLATING: TIN/LEAD PLATED OVER NICKEL

ELECTRICAL

CURRENT RATING: 0.5 AMP.

DIELECTRIC WITHSTANDING VOLTAGE: 500 VAC MIN.

INSULATION RESISTANCE: 1000 MEGAOHMS MIN.

CONTACT RESISTANCE: 30 MILLIOHMS MAX.

ENVIRONMENTAL

TEMPERATURE RANGE: -55°C TO +85°C.

DIMENSION TABLE

Circuits	Dimension			Circuits	Dimension		
	A	B	C		A	B	C
2	1.00	3.1	4	20	19.00	21.1	22
3	2.00	4.1	5	21	20.00	22.1	23
4	3.00	5.1	6	22	21.00	23.1	24
5	4.00	6.1	7	23	22.00	24.1	25
6	5.00	7.1	8	24	23.00	25.1	26
7	6.00	8.1	9	25	24.00	26.1	27
8	7.00	9.1	10	26	25.00	27.1	28
9	8.00	10.1	11	27	26.00	28.1	29
10	9.00	11.1	12	28	27.00	29.1	30
11	10.00	12.1	13	29	28.00	30.1	31
12	11.00	13.1	14	30	29.00	31.1	32
13	12.00	14.1	15	31	30.00	32.1	33
14	13.00	15.1	16	32	31.00	33.1	34
15	14.00	16.1	17	33	32.00	34.1	35
16	15.00	17.1	18	34	33.00	35.1	36
17	16.00	18.1	19	35	34.00	36.1	37
18	17.00	19.1	20	36	35.00	37.1	38
19	18.00	20.1	21				

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±
.X ± 0.30
.XX ± 0.20
.XXX ± 0.10
ANG ±



ORDER INFORMATION

FPA-SL2L-xx-LF

SERIES L LEADFREE
02~36WAY
L TYPE FOOT
DUAL CONTACT
NON ZIF

DESCRIPTION: FPC/FFC 1.0 PITCH NON ZIF SIDE ENTRY DUAL CONTACT DIP TYPE - STANDARD PCP