

NOTES:

1. ALL DIMENSIONS ARE "mm".
2. THE PRODUCT MUST BE COMPLY WITH THE DIRECTIVE OF ROHS.

ELECTRICAL TESTING:

1. 100% OPEN/SHORT TEST
2. CONTACT RESISTANCE: 5mΩ
3. INSULATION RESISTANCE: 5MΩ Min

NO.	ITEM.	DESCRIPTION	Q'TY	UL/CSA No.
1	WIRE:	UL1007 #26 紅	1PCS	E108485
2	WIRE:	UL1007 #26 黑	1PCS	E108485
3	HOUSING:	PH-H-02	2PCS	E149293
4	TERMINAL:	PH-T-26	4PCS	
5				
6				
7				
8				
9				

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS


UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

PPOJECTION



ORDER INFORMATION

PHX2-020226-F15C-LF

SERIES | LEADFREE
150mm
FEMALE TO FEMALE
26 AWG
2 TO 2 WAY

DESCRIPTION: CABLE ASS'Y