




Recommended P.C.B Layout

MATERIAL

Contact Pin : Brass
Green Product (30% Glass fiber PBT)
0.4u"Average Gold flash
Black Insulator

SPECIFICATION

Current Rate : 3 AMP
Insulation Resistance : 5000MΩMin. at DC 500V
Contact Resistance : 20mΩMax. at DC 100mA
Dielectric Voltage : AC 500V for one minute
Operation Temperature : -40°C to + 105°C

☆ Special Type

POLES	DIM A	DIM B	DIM C
☆ 6	12.66	10.26	5.08
6	15.20	12.80	5.08
☆ 8	15.20	12.80	7.62
8	17.78	15.48	7.62
10	20.30	18.10	10.16
12	22.84	20.64	12.70
14	25.38	23.18	15.24
16	27.92	25.72	17.78
20	33.00	30.80	22.86
24	38.08	35.88	27.94
26	40.62	38.42	30.48
30	45.70	43.50	35.56
34	50.80	48.58	40.64
40	58.40	56.20	48.26
44	63.48	61.28	53.34
50	71.10	68.90	60.96
56	78.72	76.52	68.58
60	83.80	81.60	73.66
64	88.88	86.68	78.74

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1


DATE

SIZE A4

TOLERANCES ARE

X. ±
.X ± 0.30
.XX ± 0.20
.XXX ±
ANG ±

P PROJECTION



ORDER INFORMATION

B-D-xx-LF
SERIES | LEADFREE
06~64WAY
DIP 180°

DESCRIPTION: BOX HEADER 2.54*2.54mm, STRAIGHT TYPE,