

Features:

- 2 ~ 12 circuits available
- Pin materail: Tin-plated brass
- Recommended PCB thickness: .070"(1.78mm) Max.

Specification:

- Current rating: (Used with #18 AWG)





Circuits	2 ~ 3	4 ~ 6	7 ~ 10	11 ~ 12
Ampere	9 A	8 A	7 A	6 A

- Voltage rating: 600V (R.M.S.)
- Contact resistance: 10mΩ Max.
- Insulation resistance: 1000mΩ min
- Dielectric withstanding voltage: 1500V AC/minute
- Ambient temperature range: -40°C ~ 105°C

Dimensional Information (mm)

Circuits	Dim. A	Dim. B
N	$4.2 \times (N - 1)$	$4.2 \times N + 1.2$

&& N = 2 ~ 12



P.C.B. hole dimensions

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

TOLERANCES ARE


X. ±

.X ±

.XX ±

.XXX ±

ANG ±



ORDER INFORMATION

MF-PDX-1Xxx-LF
SERIES LEADFREE
1X02:02WAY
1X12:12WAY
NON POST
DIP 180°
MALE

DESCRIPTION: