

RECOMMENDED P.C.BOARD HOLE DIMM.

Specifications

Current Rating: 7A AC, DC
 Voltage Rating: 250V AC Maximum
 Operating Temp: -25°C ~ +85°C
 Contact Resistance: 10mΩ Max
 Insulation Resistance: 1000mΩ Min
 Terminal Material: Brass/Tin-plated
 Material: Nylon 66, UL94V-0

Poles	Dimension mm (in.)		Part No.	Note.
	A	B		
2	3.96 (0.156)	7.92 (0.312)		
3	7.92 (0.312)	11.92 (0.469)		
4	11.88 (0.468)	15.84 (0.624)		
5	15.84 (0.624)	19.84 (0.781)		
6	19.80 (0.780)	23.80 (0.937)		
7	23.76 (0.935)	27.88 (1.098)		
8	27.72 (1.074)	31.74 (1.250)		
9	31.68 (1.247)	35.86 (1.412)		
10	35.64 (1.403)	39.90 (1.571)		
11	39.60 (1.559)	43.84 (1.726)		
12	43.56 (1.715)	47.92 (1.887)		
13	47.52 (1.871)	51.72 (2.036)		
14	51.48 (2.027)	55.92 (2.202)		

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

X, ±
 X ± 0.50
 .XX ± 0.35
 .XXX ±
 ANG ±

PJECTION



ORDER INFORMATION

VHX2-MS-xxxx-LF

SERIES

LEADFREE

0202:02 TO 02 WAY

1414:14 TO 14 WAY

SLIM

MALE TO MALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: 3.96mm Wire-to-Board Header DIP 180° Type Double