

	A	COLOR	B	C
Twist	3	BLACK	4	
	5	GREEN	3	
	7	WHITE	2	
Twist	9	RED	1	
	4	BLACK		4
	6	GREEN		3
	8	WHITE		2
	10	RED		1

NO.	ITEM.	DESCRIPTION	Q'TY
1	CABLE:	UL2725#28*1P(GREEN, WHITE)+#24*2C(RED, BLACK) +ADB JACKET:BLACK	2PCS
2	HOUSING:	PVK-H-2X05	1PCS
3	TERMINAL:	PVK-T-22	8PCS
4	KEY:	PV KEY BLACK	1PCS
5	HOUSING:	MCG-H-1X04	2PCS
6	TERMINAL:	MCG-T-24	8PCS
7	SHRINK TUBE:	5.0Φ*20mm RSFR-H BLACK	4PCS
8			
9			
10			

NOTES:


1. ALL DIMENSIONS ARE "mm".
2. THE PRODUCT MUST BE COMPLY WITH THE DIRECTIVE OF ROHS.

ELECTRICAL TESTING:

1. 100% OPEN/SHORT TEST
2. CONTACT RESISTANCE: 5mΩ
3. INSULATION RESISTANCE: 5MΩ Min

RoHS Compliant

TOLERANCES ARE



ORDER INFORMATION

MCGPVKX21-04B052428R1BK-F12N

SERIES

305mm  
FEMALE TO FEMALE  
BLACK  
ROUND CABLE  
24 /28 AWG  
04 TO 10 WAY

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X.±  
.X±  
.XX±  
.XXX±  
ANG ±

PJECTION

DESCRIPTION: CABLE ASS'Y