

Symbol 标号	Item 项目	Specification 规格
N	No. of Conductors(导体芯数)	POSITION
P	Pitch(间距)	1.0±0.10
TP	Total Pitch(总间距)	8.0±0.15
W	Width(总宽度)	10.0±0.15
M	Margin(边缘宽度)	1.0±0.15
L	Total Length(总长度)	CABLE LENGTH
T	Insertion Thickness(插入厚度)	0.303±0.05
ST	FFC Body Thickness(线身厚度)	0.121±0.03
S1/S2	Conductor Strip Length(裸铜长度)	4/4±1.0
B1/B2	Supporting tape Length(补强板长度)	6/6±2.0
Cw	Conductor Width(导体宽度)	0.65±0.03
Ct	Conductor Thickness(导体厚度)	0.035±0.005
Ft	Insulation Film Thickness(绝缘膜厚度)	0.043±0.005
Bt	Supporting tape Thickness(补强板厚度)	0.225±0.005
A1	Slanting(线口倾斜度)	<0.5

**ELECTRICAL CHARACTERISTICS**

Conductor Resistance: JISC-3102(at20°C) 2.20 Ω/M Max.

Insulation Resistance: Apply the voltage of DC 500V  
for one minute 100MΩ Min.

Dielectric Strength: Apply AC 500V for one minute.

Continuity Test: Apply microtest machine No Open/Short

Rated voltage & temperature:UL20624 60V 80°C

**Material**

Insulation: Flame Retardant Polyeste

Color: White

Conductor: Copper with 1u m min.tin-Plating

Supporting Tape: Flame Retardant Polyester

Color: Blue

4	FFC-ST-0.225*12 环保ROHS	26	mm
3	FFC-CN-0.035*0.65 环保ROHS	0.657304375	g
2	FFC-FD-0.043*120 环保ROHS	W=10 L=96mm	mm
1	FFC-FM-0.043*120 G-NS 环保ROHS	W=10 L=96mm	mm
序号	品名/规格	用量	单位

**RoHS Compliant**

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT/mm SCALE 1:1


DATE

SIZE A4


TOLERANCES ARE

X. ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±

PJECTION



**ORDER INFORMATION**



DESCRIPTION: