




Note:

1.Material:

1.1 Insulator: High temperature thermoplastic with g.f,UL94v-0

1.2 Contact: Copper alloy,t=0.20mm

1.3 Shell: Spcc,t=0.30mm

2.Specification:

2.1 Current rating: 1 A Max.

2.2 Dielectric withstanding

voltage: 750 V(ac) for 1 min.

2.3 Contact resistance: 30 mΩ Max.

2.4 Insulation resistance: 1000 MΩ Min.

2.5 Total mating force: 7.0 Kgf Max.

2.6 Total unmating force: 1.5 Kgf Min.

2.7 Temperature range: -55°C~85°C

PART NO	A±0.25	B±0.20	C±0.20	D±0.20	E±0.30	F±0.25	G±0.25	H±0.05	I±0.10
DC-S-09	30.81	24.99	16.35	7.9	17.5		12.55	2.77	2.84
DC-S-15	39.25	33.32	24.51	7.9	17.5		12.55	2.77	2.84
DC-S-25	53.04	47.04	38.35	7.9	17.5		12.55	2.77	2.84
DC-S-37	69.50	63.50	54.84	7.9	17.5		12.55	2.77	2.84

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X. ±
.X ± 0.30
.XX ± 0.20
.XXX ± 0.10
ANG ±



ORDER INFORMATION

DC-S-xx-LF
SERIES | LEADFREE
09~37 WAY
FEMALE

DESCRIPTION: D TYPE CRIMP FEMALE