




備註/Note:

1.安規/Safety:

- 1-1.規格/Rating:DC 30V/2A
- 1-2.絕緣阻抗/Insulation Resistance:500M ohm Min at DC 100V
- 1-3.絕緣耐壓/Dielectric Withstanding Voltage:AC 250V for 1 minute
- 1-4.接觸阻抗/Contact Resistance :30m ohm or less

2.材質/Material:

- 2-1.端子/PIN:磷銅/PHOSPHOR BRONZE;鍍金/金 10u"
- 2-2.膠芯/HOUSING:NYLON
- 2-3.鐵殼/SHELL:不鏽鋼/STAINLESS STEEL
- 2-4.塑膠外套/HOOD:NYLON+GF

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X. ±
.X ±
.XX ±
.XXX ±
ANG ±



ORDER INFORMATION

MSB-PA-4H2-LF
SERIES | LEADFREE
4 PIN H2 TYPE
ASSEMBLY
MALE

DESCRIPTION: MINI USB 公端成品(雙防呆)