



1. Contact Figure

CONN. 1			CONN. 2			CONN. 3		
1	Red	紅	1	Red	紅	1		
2	White	白	2					
3	Green	綠	3					
4	Black	黑	5	Black	黑	4		
SHELL			SHELL					

2. ELECTRICAL PROPERTIES

- A. Hi-Pot: 300V
- B. Contact Resistance: 5Ω
- C. Insulation Resistance: 5MΩ

7	Packing			PCS
6	Outer Mold	45P PVC COLOR:RED	A/R	G
5	Outer Mold	45P PVC COLOR:BLACK	A/R	G
4	Connector	MICRO 5P Male Nickel Plated 模號:H016	1	PCS
3	Connector	USB A Male Nickel Plated 模號:H003 & H005	1	PCS
2	CABLE	26#*2C OD:3.0MM COLOR:BLACK UL2725	A/R	MM
1	CABLE	30#*1P+26#*2C+AL+32B OD:4.5MM COLOR:BLACK UL2725	A/R	MM
序號	部品名稱	規格描述	用量	單位

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PJECTION

X.±
.X±
.XX±
.XXX±
ANG±



ORDER INFORMATION

MIBUBX12-5B4A2630-M1M1-LF

SERIES

LEADFREE
1100mm
MALE TO MALE
26,30 AWG
5 PIN B TO 4 PIN A TYPE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: