



WIRE ARRANGEMENT			
P1	COLOR	P2	P3
1	WHITE		2
2	RED	1	
3	BRAID SHIELD	3	3

6.	PLASTIC HOOD COLOR LIGHT GREEN PVC 45P.
5.	PLASTIC HOOD COLOR PINK PVC 45P.
4.	PLASTIC HOOD COLOR BLACK PVC 45P.
3.	STEREO JACK:ø3.5mm, THREE POLE, INSULATOR:BLACK.
2.	STEREO PLUG:ø3.5x26.5mm, THREE POLE, INSULATOR:BLACK.
1.	CABLE: UL2547 28AWGx2C+S,PVC JACKET BLACK.OD=2.8mm.
NO.	NOTES:

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES  
煜倫股份有限公司  
www.morethanall.com

RoHS Compliant		TOLERANCES ARE
DRAWING BY CY	SCALE 1:1	X.±
CHECKED BY GENIUS		.X±
UNIT/ mm		.XX±
DATE		.XXX±
SIZE A4		ANG±
P PROJECTION		



ORDER INFORMATION			
PNX12-030328-E20C-LF			
SERIES	200mm	LEADFREE	
		MALE TO FEMALE	
	28AWG		
	03 PIN TO 03 PIN		

DESCRIPTION: