

P.C.B.LAYOUT

ELECTRICAL CHARACTERISTICS :

CONTACT CURRENT RATING : 1AMPERES.
 DIELECTRIC WITHSTANDING VOLTAGE : AC 500V R.M.S.
 INSULATION RESISTANCE : 500 MEGOHMS MINIMUM AT DC 500V.
 CONTACT RESISTANCE : 30 MILLIOHM MAXIMUM.
 OPERATING TEMPERATURE : -55°C TO+105°C.

MECHANICAL CHARACTERISTICS :

CONTACT INSERTION FORCE : 3.0 KG MAXIMUM.
 CONTACT SEPARATION FORCE : 1.5 KG MINIMUM.

MATERIALS :

CONTACT :BRASS
 INSULATOR : P.B.T+ G.F.25% UL 94-VO RATED, L.C.P OR NL 6T.
 SHELL : BRASS.

FINISHES :

CONTACTS :GOLD FLASHED ON MATING END,TIN-LEAD
 ON TERMINATION END.
 SHELL :TIN

RoHS Compliant

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT/ mm SCALE 1:1


DATE

SIZE A4

TOLERANCES ARE

X. ±
 .X ± 0.38
 .XX ± 0.25
 .XXX ±
 ANG ±

P PROJECTION



ORDER INFORMATION

1394-SU-06-LF
 SERIES | LEADFREE
 | 06 WAY
 | UPRIGHT
 | FEMALE

DESCRIPTION: IEEE 1394-6PIN側向90°DIP(F)