



NOTE:

1. MATERIAL:

- 1-1.INSULATION: THERMOPLASTIC  
UL94V-0(PBT 30% GLASS FIBER)
- 1-2.CONTACT:BRASS
- 1-3.SHELL:BRASS
- 1-4.ORING:NBR

2.PLATING

- 2-1.CONTACT:10u" GOLD,
- 2-2.Shell:NICKEL 100u"

3. SPECIFICATION

- CURRENT: 2 A.
- OPERATING TEMPERATURE: -20° C TO 105° C.
- INSULATION RESISTANCE: 1000 MEGOHMS MIN.
- DIELECTRIC STRENGTH: 500V AC MIN.

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES  
**煜倫股份有限公司**

DRAWING BY CY  
CHECKED BY GENIUS  
UNIT / mm SCALE 1 : 1  
DATE

X. ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±



ORDER INFORMATION

M12-PS-06-LF  
SERIES | LEADFREE  
| 06 WAY  
| SOLDER  
MALE

www.morethanall.com

SIZE A4

PJECTION

DESCRIPTION: 防水頭6PIN(M)線端